

# ADVANTAGE<sup>®</sup>

COMMERCIAL TRUCK TIRES



**ECOSAFE**

*Performance Guaranteed<sup>™</sup>*

***Engineered to Perfection<sup>™</sup>***

*Quality Speaks for Itself<sup>™</sup>*

***Experience the Difference<sup>™</sup>***

**100%  
FREE  
REPLACEMENT  
WARRANTY**

# AV3000T

- **Shallow Tread Highway Tire For Trailer And All-Position Service.**
- Wide 5-rib tread design for improved stability and handling.
- Steel belts for toughness, stability, and longer, uniform wear.



TIRE SIZE	LOAD INDEX SINGLE/DUAL	SPEED SYMBOL	PLY RATING	OUTSIDE DIAMETER (INCHES)	SECTION WIDTH (INCHES)	TREAD DEPTH (32NDS)	LOAD CAPACITY (LBS) SINGLE/DUAL	REVS PER MILE
<b>TUBELESS - BSW</b>								
ST235/85R16	126/121	M	14	30.8	9.3	12	3750/ 3415	—
<b>Note: ST235/85R16 above requires special high load capacity wheel and high pressure tire valve.</b>								
*11R22.5	144/142	M	14	41.0	11.0	13	6175/ 5840	507
*11R22.5	146/143	M	16	41.0	11.0	13	6610/ 6005	507
*295/75R22.5	144/141	L	14	39.8	11.7	13	6175/ 5675	522
*11R24.5	146/143	L	14	43.0	11.0	13	6610/ 6005	483
*11R24.5	149/146	L	16	43.0	11.0	13	7160/ 6610	483
285/75R24.5	144/141	L	14	41.1	11.1	13	6175/ 5675	505

**\*Smartway Verified**



- **Premium All-Position Steel Radial Highway Service.**
- Specially designed for steer axles and all-position usage.
- 5-rib tread design for premium handling and long life.

# AV5000S

TIRE SIZE	LOAD INDEX SINGLE/DUAL	SPEED SYMBOL	PLY RATING	OUTSIDE DIAMETER (INCHES)	SECTION WIDTH (INCHES)	TREAD DEPTH (32NDS)	LOAD CAPACITY (LBS) SINGLE/DUAL	REVS PER MILE
<b>TUBELESS - BSW</b>								
215/75R17.5	135/133	J	16	30.3	8.4	16	4805/ 4540	684
235/75R17.5	143/141	J	16	31.3	9.2	16	6005/ 5675	664
225/70R19.5	125/123	M	12	32.1	8.9	16	3640/ 3415	647
225/70R19.5	128/126	M	14	32.1	8.9	16	3970/ 3750	647
245/70R19.5	135/133	M	16	33.1	9.8	16	4805/ 4540	628
265/70R19.5	140/138	M	16	34.1	10.3	16	5512/ 5203	569
255/70R22.5	140/137	M	16	37.7	10.0	16	5510/ 5070	551
275/70R22.5	148/145	L	16	37.7	10.9	16	6940/ 6395	551
*11R22.5	144/142	M	14	41.2	11.0	18	6175/ 5840	504
*11R22.5	148/145	M	16	41.2	11.0	18	6944/ 6393	504
*295/75R22.5	144/141	L	14	40.2	11.7	18	6175/ 5675	517
*295/75R22.5	146/ 143	L	16	40.2	11.7	18	6610/ 6005	517
315/80R22.5	160/154	M	20	42.4	12.3	20	10000/ 8270	476
*11R24.5	146/143	L	14	43.1	11.0	18	6610/ 6005	482
*11R24.5	149/146	L	16	43.1	11.0	18	7160/ 6610	482
285/75R24.5	144/141	L	14	43.1	11.1	18	6175/ 5675	482

**\*Smartway Verified**

# AV950DT

- Premium Traction Tire For Drive Position/Utility Vehicles.
- Pinned for studs for extreme weather conditions. (TSMI 15)
- Steel belts for toughness, stability, and longer, uniform wear.
- Designed for excellent traction and stability.

TIRE SIZE	LOAD INDEX SINGLE/DUAL	SPEED SYMBOL	PLY RATING	OUTSIDE DIAMETER (INCHES)	SECTION WIDTH (INCHES)	TREAD DEPTH (32NDS)	LOAD CAPACITY (LBS) SINGLE/DUAL	REVS PER MILE
<b>TUBELESS - BSW</b>								
225/70R19.5	125/123	M	12	32.1	8.9	19	3640/ 3415	647
225/70R19.5	125/123	M	14	32.1	8.9	19	3640/ 3415	647
245/70R19.5	135/133	M	16	33.1	9.8	19	4805/ 4540	628

# AV9000D

- Premium Closed Shoulder Steel Radial Drive Position.
- Stable belt package for outstanding wear in long haul applications.
- Designed for durability and traction with deep tread to resist stone drilling.



TIRE SIZE	LOAD INDEX SINGLE/DUAL	SPEED SYMBOL	PLY RATING	OUTSIDE DIAMETER (INCHES)	SECTION WIDTH (INCHES)	TREAD DEPTH (32NDS)	LOAD CAPACITY (LBS) SINGLE/DUAL	REVS PER MILE
<b>TUBELESS - BSW</b>								
*11R22.5	144/142	M	14	41.9	11.0	28	6175/ 5840	496
*11R22.5	148/145	M	16	41.9	11.0	28	6610/ 6005	496
*295/75R22.5	144/141	L	14	40.8	11.7	28	6175/ 5675	509
*295/75R22.5	146/143	L	16	40.8	11.7	28	6610/ 6005	509
*11R24.5	146/143	L	14	43.7	11.0	28	6610/ 6005	475
*11R24.5	149/146	L	16	43.7	11.0	28	7160/ 6610	475
285/75R24.5	144/141	L	14	41.9	11.1	28	6175/ 5675	501

\*Smartway Verified

# AV9200D

- Premium Open Shoulder Steel Radial Drive Tire
- Five full traction ribs for outstanding performance in mud and snow applications.
- Deep tread for long wear, cap base construction for enhanced casing durability.

PER TIRE SIZE	LOAD INDEX SINGLE/DUAL	SPEED SYMBOL	PLY RATING	OUTSIDE DIAMETER (INCHES)	SECTION WIDTH (INCHES)	TREAD DEPTH (32NDS)	LOAD CAPACITY (LBS) SINGLE/DUAL	REVS PER MILE
<b>TUBELESS - BSW</b>								
11R22.5	148/145	M	16	41.9	11.0	28	6945/ 6395	501
11R24.5	149/146	L	16	43.7	11.0	28	6610/ 6005	475

**NEW**



# ADVANTA MEDIUM RADIAL TRUCK LIMITED WARRANTY

## 100% FREE REPLACEMENT WARRANTY

API hereby warrants every new Advanta® Medium Radial Truck tire bearing a complete description as required by DOT and manufactured AFTER August 1, 2014 (DOT date code 3414) is warranted for workmanship and material related conditions for the life of the original tread of a new tire less 2/32". The life of the original usable tread ends when the tire tread has worn down with only 2/32" remaining, at which point the tire is considered to be fully worn out. API will refund the cost of a replacement Advanta® Medium Radial Truck tire. All Exclusions listed below void this 100% Free Replacement Warranty. Conditions and coverage are subject to change at any time and without notice.

- A) The Advanta® Medium Radial Truck tire must be replaced with a comparable new Advanta Medium Radial Truck tire by an authorized Advanta dealer. Copy of invoice will be required.
- B) Submission of claims covered by this warranty constitutes adherence to the terms of this warranty as detailed herein.
- C) Tires produced prior to August 1, 2014 (DOT date code 3314 and earlier) will be credited based on prorated tread depth remaining.
- D) Cost of mounting and balancing will be refunded up to a maximum of \$16.00 per tire. Written proof of these costs will be required.
- E) 100% free replacement applies to new first quality tires only that are manufactured after DOT date code 3414. Blemished tires, retreads and road hazard tires are specifically excluded regardless of date of manufacture.
- F) Adjustments on ride complaints or out of round tires are excluded from this warranty if they are worn past 2/32" from the original usable tread of the new tire.

## CASING WARRANTY

- A) Casings of Advanta Medium Radial Truck Tires are warranted against defects in workmanship and material through the life of the second retread. The life of the second retread is considered to end when the remaining tread on the second retread reaches a buffing stage of 2/32" or less.
- B) If an examination shows that a casing of an Advanta Medium Radial Truck Tire failed due such a defect, API will give a credit toward the purchase price of a comparable new Advanta® Medium Radial Truck Tire in the amount indicated below:

All 17.5 inch rim sizes:	\$30.00	All 19.5 inch rim sizes:	\$30.00
255/70R22.5, 275/70R22.5:	\$65.00	11R22.5, 12R22.5, 295/75R22.5, 295/80R22.5:	\$90.00
11R24.5, 285/75R24.5:	\$90.00	315/80R22.5, 385/65R22.5, 425/65R22.5:	\$85.00

Above casing warranty valid only for first five (5) years after date of manufacture of original tire.

## EXCLUSIONS

- A) All Advanta Medium Radial Truck warranties are limited to the original purchaser and the original vehicle on which they are mounted for a period of two (2) years from the date of purchase, and are not assignable to subsequent purchasers or vehicles.
- B) The Advanta® Medium Radial Truck warranties are applicable only in the United States and Canada and any tire used or equipped on a vehicle registered or operated outside the United States and Canada are not covered by this warranty.
- C) The following is not covered by the Advanta® Medium Radial Truck Warranty:
  - 1) Tire branded or marked "Non-Adjustable" (N/A) or "Blemished" (Blem), or previously adjusted.
  - 2) Failure, damage or irregular wear due to:
    - a) road hazards (i.e. puncture, cut, snag, impact breaks, etc.), wreck, collision;
    - b) fire, accident or vandalism;
    - c) mechanical condition of vehicle, including improper alignment, improper inflation, wheel imbalance, faulty shocks or brakes;
    - d) overloading the tire beyond maximum load capacity stated on the sidewall;
    - e) misapplication of tire, use of improper inner tube;
    - f) alteration of the tire or addition of alien material or transfer from one vehicle to another; and radial truck tire failed due to faulty retreading or material.
  - 3) Cost of mounting and balancing service except as noted above.
  - 4) Loss of time or use, inconvenience, or any incidental damages to include cost of towing or transportation, related property damage or consequential damages of any type or nature except as prohibited by law.
  - 5) Tires older than five (5) years from the date of manufacture as determined by the DOT/Serial number.

## OWNERS OBLIGATIONS

In order to be eligible for Advanta Medium Radial Truck Warranty service, the owner must:

- A) present the tire to an authorized dealer from which the original purchase was made;
- B) present proof of purchase to the satisfaction of the dealer;
- C) complete and sign an API Warranty Claim Form, which is available at any authorized dealer; and
- D) pay the amount due on a new tire, less the amount of credit, including taxes, mounting and balancing charges or cost of other services ordered.

## DISCLAIMER

This warranty, or any warranty stated or referred to herein, is exclusive and in lieu of any other warranty regarding the quality of Advanta Medium Radial Truck Tires, whether expressed or implied, and remedies for breach thereof shall be limited to those specifically provided herein.

# AV7000L

- Premium Open Shoulder Steel Radial Drive Position.
- Improved siping provides excellent and prolonged traction.
- Drive position traction tire designed specifically for durability.



TIRE SIZE	LOAD INDEX SINGLE/DUAL	SPEED SYMBOL	PLY RATING	OUTSIDE DIAMETER (INCHES)	SECTION WIDTH (INCHES)	TREAD DEPTH (32NDS)	LOAD CAPACITY (LBS) SINGLE/DUAL	REVS PER MILE
<b>TUBELESS – BSW</b>								
11R22.5	144/142	M	14	41.5	11.0	26	6175/ 5840	501
11R22.5	148/145	M	16	41.5	11.0	26	6610/ 6005	501
295/75R22.5	144/141	L	14	40.1	11.7	26	6175/ 5675	518
11R24.5	146/143	L	14	43.4	11.0	26	6610/ 6005	479
11R24.5	149/146	L	16	43.4	11.0	26	7160/ 6610	479
285/75R24.5	144/141	L	14	41.5	11.1	26	6175/ 5675	501



## SmartWay™ TIRES

The Environmental Protection Agency's (EPA) has tested and verified the performance of vehicles, technologies and equipment that have the potential to lower greenhouse gases and other air pollutants from freight transport.

## ECOSAFE™ TIRES

AMERICAN PACIFIC INDUSTRIES has integrated Ecosafe technology into the design and development of ADVANTA MEDIUM TRUCK tires. Ecosafe technology reduces rolling resistance and increases fuel efficiency. This process lowers vehicle emissions, which helps to sustain a healthier planet.

# AV8000M

- Extra Deep Tread Multi-Service Tread Design.
- Chip cut resistant compound for on/off road service.
- Steel belts built for durability, strength and toughness.
- Extra wide tread face for improved stability.



TIRE SIZE	LOAD INDEX SINGLE/DUAL	SPEED SYMBOL	PLY RATING	OUTSIDE DIAMETER (INCHES)	SECTION WIDTH (INCHES)	TREAD DEPTH (32NDS)	LOAD CAPACITY (LBS) SINGLE/DUAL	REVS PER MILE
<b>TUBELESS – BSW</b>								
11R22.5	146/143	M	16	41.4	11.0	22	6610/ 6005	502
315/80R22.5	160/154	J	20	42.9	15.3	23	10000/ 8270	486
11R24.5	149/146	L	16	43.5	11.0	22	7160/ 6610	478

**Performance Guaranteed™**  
**Engineered to Perfection™**

**Tire Construction and Benefits: The ADVANTA Medium Radial Truck tires offer major construction differences over other Chinese tire designs:**

- The **ADVANTA** truck tire has a state-of-the-art sidewall profile and steel belt package resulting in even contact pressure with the surface of the road. This feature promotes enhanced handling, stability and uniform wear.
- **ADVANTA** tires are manufactured with cap/base construction which enhances casing durability, resulting in greater heat dissipation, multiple retreads and lower running costs.
- **ADVANTA** tread compounds are formulated with the latest technological advances to ensure maximum performance and durability for every application.
- **ADVANTA** tires utilize a two-compound filler in the bead contour which facilitates a more exact, concentric fitment in the mounting process. This results in greater overall uniformity and virtually eliminates vibration problems, regardless of the application.
- **ADVANTA** tires are constructed with a proprietary wire wrap within the steel belt package resulting in less overall tread movement and a wider footprint. This feature promotes stability, durability and long-lasting performance.

Currently, the Advanta Medium Truck Product Line offers tires to fit nearly every application:

- AV3000T** *Premium All Position tire designed for Trailer applications.*
- AV5000S** *All Position Steer design for regional applications.*
- AV7000L** *Premium Open Shoulder Drive tire.*
- AV8000M** *All Position Multi use Chip and Cut resistant for On/Off Road applications.*
- AV950** *Premium Traction tire Designed for Utility vehicles.*
- AV9000D** *Premium Closed Shoulder drive Design for Long Haul applications.*
- AV9200D** *Premium Open Shoulder Steel Radial Drive Tire.*

As with all American Pacific Industries, Inc. Products, we offer a most comprehensive warranty program, including an individual adjustment policy and liability insurance coverage (*See Warranty page for details*). This will assure your sales force and customers of getting the very best Medium Radial Truck tire available today.

**Try the new ADVANTA Medium Radial Truck Tire  
and see the difference for yourself.**

**ADVANTA®**

(800) 944-8414 • [www.apitire.com](http://www.apitire.com)

**Quality Speaks For Itself™ • Experience The Difference™**